Washer extractor

WX6-60

Priority on people

Compass Pro® microprocessor offers:

- Large display and one control knob for easy program selection
- Language selection
- Quick selection and option buttons for the most frequently used wash programs and options

Long-term savings

- Extremely low water and energy consumption – see table below
- High extraction force for efficient dewatering
- Super Balance guarantees the correct extraction force
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection



Images shown are a representation of the product only and variations may occur.

Main options and accessories

- Stainless steel side panels
- Five compartment supply injector

Main specifications		WX6-60	
Rated capacity, filling factor 1:10	kg/lb	60 / 135	
Drum, volume	litre	600	
Drum, diameter	ø mm	980	
Extraction	rpm	630	
G-factor		220	
Heating alternatives, 400V	electricity, kW	38.0	
Consumption data "Normal 60°C" Economy[1]			
		Full load, 60 kg	Half load, 30 kg
Total time	Min	51	49
Water consumption (cold+hot)	litre	380+100	360+80
Energy consumption (motor/heating/hot water)	kWh	0.75/2.85/6.4	0.7/2.3/5.1
Residual moisture	%	60	66

1. Water temperature 15°C cold water and 65°C hot water.

Produced according to ISO 9001 and ISO 14001.
Certified with CB certificate for Low Voltage Directive and S-mark according to the Machinery Directive. Protection class IP X4D.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated	380–400V 3~	50	38.4	40.3	63
	415V 3~	50	38.4	40.3	63

Water connection		WX6–60
Water valves	DN	25
Water pressure	kPa	200–600
Capacity at 300 kPa	l/min	110
Drain valve	ø mm	75
Draining capacity	l/min	170
Floor requirements		
Frequency of the dynamic force	Hz	10.5
Floor load at max extraction	kN	10 ± 15.6
Sound levels		
Sound power/pressure level at extraction[1]	dB(A)	83/66
Sound power/pressure level at wash[1]	dB(A)	69/52
Heat emission		
% of installed power, max		5
Shipping data[2]		
Weight	net, kg	775
Shipping volume	m^3	3.2

1. Operating panel
2. Door opening ø 535 mm
3. Detergent box
4. Cold water
5. Hot water
6. Drain valve
7. Liquid detergent supply
8. Electrical connection
9. Detergent supply injector, powder, right or left side (option)

1. Sound power levels measured according to ISO 60704.
2. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.





